

Version 7.1E

Page 1 / 9

Revision Date 16.04.2024

SECTION 1: Identification of the substance/mixture and of the company

Product Identifier

Product Name: SiSiB® PC12010-0.65

Chemical Name: Hexamethyldisiloxane

CAS-No.: 107-46-0

EC-No.: 203-492-7

Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For Cosmetics use

Details of the supplier of the safety data sheet

Company

Nanjing SiSiB Silicones Co., Ltd.

Guanghua Sci & Tech Industrial Zone,

No. 104, Guanghua Road, Nanjing 210007, P.R.China

Email: SDS@SiSiB.com

Emergency Telephone Number: +86-25-8468-0091

SECTION 2: Hazardous identification

Classification of the substance or mixture

Classification according to REGULATION (EC) No 1272/2008[EU-GHS/CLP]

Flammable liquids Category 2 H225

Acute aquatic toxicity Category 1 H400

Chronic aquatic toxicity Category 1 H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary statement(s):

P210

Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P273

Avoid release to the environment.

Version 7.1E	Page 2 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

P391 Collect spillage.
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/ container to an approved waste disposal plant.
Supplemental Hazard Statements none

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Substances

Synonyms HMDSO
Formula $C_6H_{18}OSi_2$
Molecular Weight 162,38 g/mol
Component Hexamethyldisiloxane
CAS-No. 107-46-0
EC-No. 203-492-7

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
Hexamethyldisiloxane		
CAS-No. 107-46-0 EC-No. 203-492-7	Flam. Liq. 2; Aquatic Acute 1; Aquatic Chronic 1; H225, H400, H410 M-Factor - Aquatic Acute: 1 - Aquatic Chronic: 1	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Version 7.1E

Page 3 / 9

Revision Date 16.04.2024

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

no data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Carbon oxides, silicon oxides

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

For personal protection see section 8.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Version 7.1E	Page 4 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

Avoid inhalation of vapor or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.

Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Store under inert gas, hygroscopic

Storage class (TRGS 510): Flammable liquids

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated

SECTION 8: Exposure Controls/Personal Protection

Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Version 7.1E	Page 5 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell

test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Form: liquid
Color	colorless
Odor	no data available
Odor Threshold	no data available
pH	no data available
Melting point/freezing point	Melting point/range: -59 °C - lit.
Initial boiling point and boiling range	101 °C - lit.
Flash point	0,6 °C - closed cup
Evaporation rate	no data available
Flammability (solid, gas)	no data available
Upper/lower flammability or explosive limits	
Upper explosion limit	21,8 %(V)
Lower explosion limit	0,5 %(V)

Version 7.1E	Page 6 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

Vapor pressure	44 hPa at 20 °C
Vapor density:	5,61 - (Air = 1.0)
Relative density	0.764 g/mL at 20 °C
Water solubility:	0.00093 g/l at 23 °C - slightly soluble
Partition coefficient: n-octanol/water	log Pow: > 4 at 25 °C
Auto-ignition temperature	340 °C at 1,013 hPa
Decomposition temperature	no data available
Viscosity	no data available
Explosive properties	no data available
Oxidizing properties	no data available
Other safety information	
Relative vapor density	5.61 - (Air = 1.0)

SECTION 10: Stability And Reactivity

Reactivity

no data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

no data available

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids, Strong bases, Strong oxidizing agents, Oxygen

Hazardous decomposition products

Other decomposition products - no data available

In the event of fire: see section 5

SECTION 11: Toxicological Information

Information on toxicological effects

Acute toxicity

LD50 Oral - rat - > 5,000 mg/kg

LC50 Inhalation - Rat - 4 h - 15956 ppm

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - > 2,000 mg/kg

(OECD Test Guideline 402)

NOAEL Oral - Rat - 160 mg/kg

Version 7.1E	Page 7 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

Chromosome aberration test in vitro

Chinese hamster lung cells

Result: negative

OECD Test Guideline 475

Rat - Bone marrow

Result: negative

Carcinogenicity

No data available

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No toxicity to reproduction

Reproductive toxicity - Rat - male and female - inhalation (vapor)

No significant adverse effects were reported

Developmental Toxicity - Rat - Inhalation

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

RTECS: JM9237000

Prolonged or repeated exposure to skin causes defatting and dermatitis., Dizziness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological Effects

Toxicity

Version 7.1E

Page 8 / 9

Revision Date 16.04.2024

Toxicity to fish:

flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - ca. 0.46 mg/l - 96 h

Toxicity to algae:

EC50 - Pseudokirchneriella subcapitata (green algae) - 0.22 mg/l - 95 h

(OECD Test Guideline 201)

Persistence and degradability

Biodegradability

aerobic - Exposure time 28 d

Result: 2 % - Not biodegradable

(OECD Test Guideline 301C)

Bioaccumulative potential

No data available

Bioaccumulation:

Cyprinus carpio (Carp) - 70 d at 25 °C

Bioconcentration factor (BCF): 1,100 - 2,400

(OECD Test Guideline 305C)

Mobility in soil

no data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Very toxic to aquatic life with long lasting effects.

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product:

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport Information

UN number

ADR/RID: 1993

IMDG: 1993

IATA: 1993

UN proper shipping name

Version 7.1E	Page 9 / 9	Revision Date 16.04.2024
--------------	------------	--------------------------

ADR/RID:	FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)	
IMDG:	FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)	
IATA:	Flammable liquid, n.o.s. (Hexamethyldisiloxane)	
Transport hazard class(es)		
ADR/RID: 3	IMDG: 3	IATA: 3
Packing group		
ADR/RID: II	IMDG: II	IATA: II
Environmental hazards		
ADR/RID: yes	IMDG Marine Pollutant: yes	IATA: no
Special precautions for user		
no data available		

SECTION 15:Regulatory Information

This safety datasheet complies with the requirements of Regulation (EC) No. 453/2010.

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16:Other Information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further information

It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.