

ADDSiL™ 1232 Leveling Agent

INTRODUCTION

ADDSiL™ 1232 is polyether modified polysiloxane which has excellent compatibility with general paint resins and has no reverse influences on recoatability.

ADDSiL™ 1232 has excellent substrate wetting, it is suitable for radiation-curing system.

ADDSiL™ 1232 can provide superb leveling and slip in solvent-borne system and water-borne system.

EFFECTS

Leveling:	★★★★★
Wetting:	★★★★★
Recoat Ability:	★★★★★
Compatibility:	★★★★
Slip effect:	★★★★
Low Foaming Stability:	★★★★
Anti-crater:	★★★★
Anti-adhesive:	★★★

PHYSICAL PROPERTIES

Color and Appearance	Light yellow viscous transparent liquid
Ingredient	Polyether modified polysiloxane
Active Content	100%

APPLICATIONS

- Solvent-borne coatings.
- Water-borne coatings
- UV coatings

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% of the total formulations.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 1232 is supplied in 25Kg pail.

ADDSiL™ 1232 Leveling Agent

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, ADDSiL™ 1232 has a shelf life of 24 months.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.