

ADDSiL™ 7002 Wetting & Leveling Agent

INTRODUCTION

ADDSiL™ 7002 is a silicone polyether block copolymer, it has a pendant molecular architecture.

PHYSICAL PROPERTIES

Color and Appearance	Colorless or yellowish transparent liquid
Viscosity (25°C), mm ² /s	800-3,000
Cloud Point, °C	40-55
Recommended Dosage, %	0.5-2.0
Active Component, %	100

BENEFITS

- Low surface tension
- Good water solubility, emulsification, foam stability and physiological inertness

APPLICATIONS

- ADDSiL™ 7002 can be used as a wetting agent and flow/leveling agent in both waterborne and solvent-borne coatings and inks.

PACKING

ADDSiL™ 7002 is supplied in 200Kg / 1000Kg plastic drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 7002 has a shelf life of 12 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for

ADDSiL™ 7002 Wetting & Leveling Agent

a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.