

KOBOND™ 8166 Dispersing Agent

INTRODUCTION

KOBOND™ 8166 is a high M.W. block style copolymer solution with pigment affinity groups.

BENEFITS / EFFECTS

- Superb performance of viscosity reduction and dispersing;
- Excellent stability without foam-inhibition in medium and high pigment carbon black system;
- Reduced viscosity and fineness;
- High performance of color hue and storage stability in solvent-free epoxy color paints

PHYSICAL PROPERTIES

Color and Appearance	Yellowish clear liquid
Solvent	Dibasic Ester
Active Ingredient	45%
Flash Point	>100°C
Density 25°C	1.07~1.11 g/ml
Viscosity 25°C	10~40s (Tu-4 viscometer)

APPLICATIONS

- Solvent-borne coatings.

RECOMMENDED DOSAGE

The recommended dosage as below:

Inorganic pigment	1~10%
Organic pigment	15~35%
Carbon black	25~100%

The additive should be incorporated into the mill base before the addition of pigments.

PACKING

KOBOND™ 8166 is supplied in 25Kg plastic pail / 180Kg steel drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

KOBOND™ 8166 Dispersing Agent

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, KOBOND™ 8166 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.