

# ADD*SiL*<sup>TM</sup> 23880

## Silicone Surfactant for Flexible Slabstock Foam

### INTRODUCTION

ADD*SiL*<sup>TM</sup> 23880 is a polyalkyleneoxide modified polysiloxane surfactant which is designed for flexible PU foam.

### SPECIAL FEATURES AND BENEFITS

- ☐ Medium-high efficiency silicone
- ☐ Provide excellent emulsification
- ☐ Wide processing latitude
- ☐ General purpose silicone with good foaming stability and breathability

### TYPICAL PHYSICAL PROPERTIES

Appearance	Viscous liquid
Viscosity 25°C	850+/-450 cst
Density 25°C	1.05 g/cm <sup>3</sup>
Flash Point °C	Min.96

### PACKING AND STORAGE

ADD*SiL*<sup>TM</sup> 23880 is supplied in net weight 210Kg steel drum or 1000Kg IBC tote.

When stored at ambient temperature in the original unopened packings, ADD*SiL*<sup>TM</sup> 23880 has a shelf life of 24 months from the date of production.

### NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

May 2024 | Technical Data Sheet | Edition SE

# **ADD*Si*L™ 23880**

## **Silicone Surfactant for Flexible Slabstock Foam**

Please send all technical questions concerning quality and product safety to:  
[support@SiSiB.com](mailto:support@SiSiB.com).