

ADDSiL™ 13808

Silicone Surfactant for Flexible Polyurethane Foam

INTRODUCTION

ADDSiL™ 13808 is a polyalkyleneoxide modified polysiloxane surfactant which is designed for flexible PU foam.

FEATURES

- Provides good breathability
- Provides fine and regular cell structure
- Low-medium potency, recommended for density min.20 Kg/m³ formulation or density 40 Kg/m³~60 Kg/m³ based TDI VE foam formulation

TYPICAL PHYSICAL PROPERTIES

Appearance	Colorless to Yellowish Clear Liquid
Viscosity 25°C	800+/200 cSt
Density 25°C	1.03 g/cm ³
Flash Point	>96 °C

PACKING AND STORAGE

ADDSiL™ 13808 is supplied in net weight 210Kg steel drum or 1000Kg IBC tote.

When stored at ambient temperature in the original unopened packing, ADDSiL™ 13808 has a shelf life of 24 months from the date of production.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

ADD*SiL*TM 13808

Silicone Surfactant for Flexible Polyurethane Foam

Please send all technical questions concerning quality and product safety to:
support@SiSiB.com.