

# ADDSiL™ 3015 Silicone Wetting Agent

## INTRODUCTION

ADDSiL™ 3015 is polyether modified organic silicone compound. It can greatly decrease the system surface tension and provide excellent substrate wetting ability, as well as low foaming stability.

## EFFECTS

Leveling:	★★★★★
Wetting:	★★★★★
Recoat Ability:	★★★★★
Compatibility:	★★★★★
Sliding	★
Low Foaming Stability:	★★★★★
Anti-crater:	★★★★★
Anti-adhesive:	★

## PHYSICAL PROPERTIES

Ingredient	Polyether Modified Silicone
Appearance	Colorless to yellowish clear liquid
Active content	100%

## APPLICATIONS

- Water-wood-paint
- Industrial water-borne coatings
- UV cure coatings
- Printing ink

## RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0%. Optimal levels should be determined through laboratory testing to achieve the best results.

## PACKING

ADDSiL™ 3015 is available in 25Kg pail or 200kg drum.

## HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

## STORAGE

When stored at temperatures between 10°C and 35°C in the original

## ADDSiL™ 3015 Silicone Wetting Agent

unopened containers, ADDSiL™ 3015 has a shelf life of 24 months from the date of production.

### NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.