

ADDSiL™ 5533 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5533 is a highly effective silicone defoamer tailored for water-based systems.

Key Features

- **Strong Defoaming Performance:** Effectively controls foam in water-based systems.
- **Low Addition Rates:** High efficiency means only small amounts are needed for optimal results.
- **Compatibility:** Designed specifically for water-based systems, ensuring seamless integration.
- **Ease of Use:** Can be added during the grinding stage for uniform dispersion and maximum effectiveness.

PHYSICAL PROPERTIES

Ingredient	Modified Polydimethylsiloxane
Appearance	Light yellow viscous liquid
Content	100%

APPLICATIONS

- Water-borne coatings
- Medium and high polarity solvent-borne coatings

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 5533 is available in 25Kg pails.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5533 has a shelf life of 24 months from the date of production.

ADDSiL™ 5533 Silicone Defoamer

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.