

# PowerCat™ A30 Amine Catalyst

## Introduction

PowerCat™ A30 is a delayed action gel catalyst used for HR Mold Foaming.

Delayed action gel catalyst; improved load building and cell opening

## Physical Properties

Appearance	Clear Liquid
Viscosity (25°C, cP)	1.1
Density (25°C, g/cm <sup>3</sup> )	1.08
Water (%)	45

## Benefits & Applications

- Delayed action load building (TDI)
- Improved flowability (MDI)
- Cell opening gel catalyst
- Low corrosion

## Handling & Storage

In accordance with good industrial practice, handle with care and avoid unnecessary personal contact. Avoid continuous or repetitive breathing of dust. Use only with adequate ventilation. Protect skin. Avoid dust formation and ignition sources.

This product may be stored up to four years in a sealed container. Containers should be stored in a cool, dry area. Extended storage at elevated temperatures or exposure to direct heat or sunlight could reduce product life. Keep containers sealed when not in use.

For more detailed information please refer to the material safety data sheet.

## Packing

PowerCat™ A30 is supplied in 200Kg drum.

## Note

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for

## PowerCat™ A30 Amine Catalyst

a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.