

SiSiB[®] AA1097

Anchorage Additive

INTRODUCTION

SiSiB[®] AA1097 is a reactive silane mixture used to enhance abrasion resistance and adhesion in solvent-based, platinum-catalyzed, emulsion-based, and tin-catalyzed release coatings. It improves the abrasion resistance of silicone release coatings and enhances their adhesion to base substrates.

TYPICAL PHYSICAL PROPERTIES

| | |
|----------------------------------|------------------------------|
| Color and Appearance | Colorless transparent liquid |
| Active content (%) | 100 |
| Density (20°C) g/cm ³ | 1.11-1.12 |
| Viscosity (25°C, mpa.s) | 2-8 |
| Flash point (°C) | 51 |
| Refractive index (25°C) | 1.42-1.43 |

APPLICATIONS

SiSiB[®] AA1097 Anchorage Additive is used to improve the abrasion resistance of silicone release coatings and enhances their adhesion to base substrates.

Optimal levels should be determined through laboratory testing to achieve the best results.

PACKING AND STORAGE

In the unopened original container, SiSiB[®] AA1097 has a shelf life of 3 years in a dry and cool place.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

SiSiB[®] AA1097

Anchorage Additive

Please send all technical questions concerning quality and product safety to:
support@SiSiB.com.