

ADDSiL™ 12250

Polyurethane Foam Stabilizer

INTRODUCTION

ADDSiL™ 12250 surfactant is a silicone stabilizer designed for cold-cure flexible molded MDI and MDI/TDI polyurethane foams.

FEATURES

- Good heat stability, chemical stability and super emulsify ability.
- Excellent foam stability and balance function.
- Wide processing latitude for open foams.
- Phthalate free, low VOC and low fogging.

TYPICAL PHYSICAL PROPERTIES

Appearance	Colorless liquid
Viscosity _{25°C}	28 +/- 10 cSt
Density _{25°C}	0.95 +/- 0.05g/cm ³
Freezing point	< 0°C

APPLICATIONS

ADDSiL™ 12250 is used as cell regulating HR foam type silicone surfactant for cold cure HR MDI and HR TDI/MDI polyurethane foams.

Typical use levels are 0.5~1.0 parts ADDSiL™ 12250 per 100 parts polyol.

PACKING AND STORAGE

ADDSiL™ 12250 is supplied in net weight 200Kg steel drum or 1000Kg IBC tote.

When stored at ambient temperature in the original unopened packings, ADDSiL™ 12250 has a shelf life of 12 months from the date of production.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further

ADD*SiL*TM 12250

Polyurethane Foam Stabilizer

developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.