

# ADDSiL™ 15293

## Silicone Surfactant

### INTRODUCTION

ADDSiL™ 15293 is silicone surfactant for most conventional rigid polyurethane foam and shoe sole systems. It provides excellent flame retardant properties in rigid foam applications and excellent cell structure in shoe sole applications.

### FEATURES

- Good stability when mixed with water and amine-catalyst.
- Good compatibility with most common polyol premixes.
- Nonhydrolyzable chemical structure for improved premix stability

### TYPICAL PHYSICAL PROPERTIES

Appearance	Hazy to clear liquid
Viscosity <sub>25°C</sub>	450+/-200 mPa.s
Density <sub>25°C</sub>	1.07+/-0.02 g/cm <sup>3</sup>
Water	Max. 0.3%
Freezing point	Max.18 °C
pH (4% water solution)	6.0+/-1.5

### APPLICATIONS

ADDSiL™ 15293 can be used in most rigid foam applications including laminated boardstock, most pour-in-place systems, spray foam, packaging and bunstock..

ADDSiL™ 15293 can be well used in sole for good synthetically performance.

Typical use levels are 1.0~2.0 parts ADDSiL™ 15293 per 100 parts polyol.

### PACKING AND STORAGE

ADDSiL™ 15293 is supplied in net weight 200Kg steel drum or 1000Kg IBC tote.

When stored at ambient temperature in the original unopened packings, ADDSiL™ 15293 has a shelf life of 12 months from the date of production.

# **ADD*SiL*<sup>TM</sup> 15293**

**Silicone Surfactant**

## **NOTES**

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: [support@SiSiB.com](mailto:support@SiSiB.com).