SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.11	Page 1 / 18	Revision Date 16 01 2021
VCI 31011 0.15	Tage 17 To	Revision Date 10.01.2021

SECTION 1: Identification of the substance/mixture and of the company

Product Identifier	
Product Name:	ADDSiL™ 8323
Relevant identified uses of the sub	stance or mixture and uses advised against
Relevant applications identified	For industrial use
Details of the supplier of the safety	data sheet
Company	Nanjing SiSiB Silicones Co., Ltd.
	Guanghua Sci & Tech Industrial Zone,
	No. 104, Guanghua Road, Nanjing 210007, P.R.China
	Email: SDS@SiSiB.com
Emergency Telephone Number:	+86-25-8468-0091

SECTION 2: Hazardous identification

Classification of the substance or mixture

SUMMARY OF HAZARD IN AN EMERGENCY SITUATION

Liquid.

Does not mix with water.Combustible.

Classification

Eye Irritation Category 2B, Skin Corrosion/Irritation Category 3

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Catalog of Hazardous Chemical; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	WARNING

Hazard statement(s)

H320 Causes eye irritation.

H316 May be harmful in contact with skin.

Precautionary statement(s) Prevention

P264 Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable.

Precautionary statement(s) Disposal



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1J

Page 2 / 18

Revision Date 16.01.2021

Not Applicable

Physical and Chemical Hazard

Liquid.

Does not mix with water.Combustible.

Toxic smoke/fumes in a fire.

Health Hazards

Inhaled

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

The low vapour pressure of silicone fluids make exposures to potentially harmful vapours unlikely. The vapours of a low molecular weight member of this family, hexamethyldisiloxane, were tolerated by guinea pigs at concentrations of 25000ppm for 30 minutes without apparent ill-effect. Higher saturated vapour concentrations (39000-40000 ppm) produced death in 15-20 minutes; deaths appeared to occur as a result of respiratory failure as animals removed from exposure, prior to death, almost always survived. Although animal studies show that silicone fluids are removed very slowly from the lungs, their presence is not expected to produce adverse effects; exposure to aerosols is unlikely to result in damage to the health. When heated at high temperatures, the fumes and oxidation products of methyl silicones can be both irritating and produce toxic effects following inhalation. Massive exposures of heated silicone oil can produce central nervous system depression leading to death.

Not normally a hazard due to non-volatile nature of product.

Ingestion

Animal studies with silicone fluids indicate that acute toxicity is very low; large doses are required to produce death. Some silicone fluids have a laxative action and may also produce central nervous system depression. Silicone fluids have been used for their defoaming and flatulence-reducing action in the gastrointestinal effect without any reported ill-effects.

Aspiration of silicone fluids or emulsions may produce chemical pneumonitis.

High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort.

The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Skin Contact

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more



SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 3 / 18	Revision Date 16.01.2021
--------------	-------------	--------------------------

after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation.

Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin

Eye

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

When the eyes of human subjects where exposed to silicone fluids, there was evidence of transitory conjunctival irritation within a few hours; this resolved within 24 hours. When applied to the eyes of rabbits, silicone fluids produced transitory irritation which lasted no longer than 48 hours. Injection into the various structures of the eye of animals produced corneal scarring, degenerative changes in the retina, foreign body reaction and cataracts.

Chronic

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Environmental Hazards

See Section 12

Other hazards

May produce skin discomfort.

SECTION 3: Composition/information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
68037-76-3	99	methyl 2-phenylpropyl dodecylmethyl siloxane copolymer

SECTION 4: First aid measures

Description of first aid measures

Eye Contact

If this product comes in contact with eyes:

Wash out immediately with water.

If irritation continues, seek medical attention.

Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

If skin contact occurs:

Immediately remove all contaminated clothing, including footwear.



SiSiB SILICONES - A part of SINOPCC group.

SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 4 / 18	Revision Date 16.01.2021
Ver 31011 0. 13	1 age 47 10	

Flush skin and hair with running water (and soap if available).

Seek medical attention in event of irritation.

Inhalation

If fumes, aerosols or combustion products are inhaled remove from contaminated area.

Other measures are usually unnecessary.

Ingestion

Immediately give a glass of water.

First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Advise for rescue team (PPE requirement for rescue personnel)

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Foam.

Dry chemical powder.

BCF (where regulations permit).

Carbon dioxide.

Water spray or fog - Large fires only.

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

Alert Fire Brigade and tell them location and nature of hazard.

Wear full body protective clothing with breathing apparatus.

Prevent, by any means available, spillage from entering drains or water course.

Use water delivered as a fine spray to control fire and cool adjacent area.

Avoid spraying water onto liquid pools.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected location.

If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard

High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers.

These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite.

An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult. Combustible.

Slight fire hazard when exposed to heat or flame.

Heating may cause expansion or decomposition leading to violent rupture of containers.



SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 5 / 18	Revision Date 16.01.2021
--------------	-------------	--------------------------

On combustion, may emit toxic fumes of carbon monoxide (CO).

May emit acrid smoke.

Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO2)

silicon dioxide (SiO2)

other pyrolysis products typical of burning organic material.

May emit corrosive fumes.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8 **Measures for Preventing Secondary Contamination** Refer to section above **Environmental precautions** See section 12 Methods and material for containment and cleaning up **Minor Spills** Slippery when spilt. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. **Major Spills** Silicone fluids, even in small quantities, may present a slip hazard. It may be necessary to rope off area and place warning signs around perimeter. Clean up area from spill, with suitable absorbant, as soon as practically possible. Final cleaning may require use of steam, solvents or detergents. Moderate hazard Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources.



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1J Page 6 / 18 Revision Date 16.01.202	1
--	---

Increase ventilation.

Stop leak if safe to do so.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.

Absorb remaining product with sand, earth or vermiculite.

Collect solid residues and seal in labelled drums for disposal.

Wash area and prevent runoff into drains.

If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7: Handling and storage

Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Prevent concentration in hollows and sumps.

Avoid smoking, naked lights or ignition sources.

Avoid contact with incompatible materials.

When handling, DO NOT eat, drink or smoke.

Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling.

Work clothes should be laundered separately.

Use good occupational work practice.

Observe manufacturer's storage and handling recommendations contained within this SDS.

Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

DO NOT allow clothing wet with material to stay in contact with skin.

Other information

Store in original containers.

Keep containers securely sealed.

No smoking, naked lights or ignition sources.

Store in a cool, dry, well-ventilated area.

Store away from incompatible materials and foodstuff containers.

Protect containers against physical damage and check regularly for leaks.

Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

Metal can or drum



SAFETY DATA SHEET

ADDSiL™ 8323

Packaging as recommended by manufacturer.

Check all containers are clearly labelled and free from leaks.

Storage incompatibility

Concentrated acids and bases cause degradation of polymer. Boiling water may soften and weaken material.

Avoid strong acids, bases.

Avoid reaction with oxidising agents

SECTION 8: Exposure Controls/Personal Protection

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ADDSiL™ 8323	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
methyl 2-phenylpropyl dodecylmethyl siloxane copolymer	Not Available	Not Available

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

Cause inflammation

Cause increased susceptibility to other irritants and infectious agents

Lead to permanent injury or dysfunction

Permit greater absorption of hazardous substances

Acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure. **Exposure controls**



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1J	Page 8 / 18	Revision Date 16.01.2021
	rage e / re	Revision Bate relenzezi

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions

to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapors, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s
	(50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed	0.5-1 m/s
conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low	(100-200 f/min.)
velocity into zone of active generation)	
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher	1-2.5 m/s
dusts, gas discharge (active generation into zone of rapid air motion)	(200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at	2.5-10 m/s
high initial velocity into zone of very high rapid air motion).	(500-2000 f/min.)
Within each range the appropriate value depends on:	

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favorable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe.

Velocity generally decreases with the square of distance from the extraction point (in simple cases).

Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source.

The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection



SAFETY DATA SHEET ADDSiL[™] 8323

Version 6.1J

Page 9 / 18

Revision Date 16.01.2021



Eye and face protection

Safety glasses with side shields.

Chemical goggles.

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.

Skin protection

See Hand protection below

Hands/feet protection

Wear chemical protective gloves, e.g. PVC.

Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can't be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

Frequency and duration of contact,

Chemical resistance of glove material,

Glove thickness and

Dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time



SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 10 / 18	Revision Date 16.01.2021
--------------	--------------	--------------------------

greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

Excellent when breakthrough time > 480 min

Good when breakthrough time > 20 min

Fair when breakthrough time < 20 min

Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material.

Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection

See Other protection below

Other protection

Overalls.

P.V.C. apron.

Barrier cream.

Skin cleansing cream.

Eve wash unit.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1J	Page 11 / 18	Revis	ion Date 16.01.2	021
Required minimum	Maximum gas/vapour concenti	ation	Half-face	Respirator
Protection factor	present in air p.p.m. (by volum	e)	Respirator	Respirator
up to 10	1000		A-AUS / Class1	-
up to 50	1000		-	A-AUS / Class 1
up to 50	5000		Airline *	-
up to 100	5000		-	A-2
up to 100	10000		-	A-3
100+				Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point

organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted.

Because of these limitations, only restricted use of cartridge respirators is considered appropriate. Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used.

SECTION 9: Physical and Chemical Properties

Appearance	Light yellow transparent liquid
Physical state	Liquid
Relative density (Water = 1)	Not Available
Odor	Not Available
Partition coefficient n-octanol / water	Not Available
Odor threshold	Not Available
Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available
Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available
Viscosity (cSt)	400-900
Initial boiling point and	Not Available
boiling range (°C)	
Molecular weight (g/mol)	Not Available
Flash point ($^{\circ}$ C)	>100
Taste:	Not Available



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1J	Page 12 / 18	Revision Date 16.01.2021
Evaporation rate	Not Available	
Explosive properties	Not Available	
Flammability	Not Applicable	
Oxidizing properties	Not Available	
Upper Explosive Limit (%)	Not Available	
Surface Tension (dyn/cm or	r mN/m) Not Available	
Lower Explosive Limit (%)	Not Available	
Volatile Component (%vol)	Not Available	
Vapor pressure (kPa)	Not Available	
Gas group	Not Available	
Solubility in water	Immiscible	
pH as a solution (1%)	Not Available	
Vapor density (Air = 1)	Not Available	
VOC g/L	Not Available	

SECTION 10: Stability And Reactivity

Reactivity

See section 7

Chemical stability

Silicone fluids are stable under normal storage conditions.

Hazardous polymerisation will not occur.

At temperatures > 150 C, silicones can slowly react with the oxygen in air.

When heated > 300 C, silicones can slowly depolymerise to volatile siloxanes whether or not air is present.

Unstable in the presence of incompatible materials.

Product is considered stable.

Hazardous polymerisation will not occur.

Possibility of hazardous reactions

- See section 7
- Conditions to avoid
- See section 7

Incompatible materials

See section 7

Hazardous decomposition products

See section 5

SECTION 11:Toxicological Information

ADDSiL[™] 8323



SAFETY DATA SHEET

ADDSiL™ 8323

		ADDSIL 0323		
Version 6.1J	Page 13 / 18	Revision Date 16.01.2021		
ΤΟΧΙΟΙΤΥ	IRR	ITATION		
Not Available	Not Available Not Available			
methyl 2-phenylpropy	/I dodecvlmethvl siloxane c	copolymer		
TOXICITY	IRR	ITATION		
Not Available	Not	Available		
Legend:				
1. Value obtained from	Europe ECHA Registered S	ubstances - Acute toxicity		
2.* Value obtained from	n manufacturer's SDS.			
Unless otherwise speci	fied data extracted from RTE	CS - Register of Toxic Effect of chemical Substances.		
METHYL 2-PHENYLP	ROPYL DODECYLMETHYL	SILOXANE COPOLYMER		
No significant acute tox	cicological data identified in lit	terature search.		
ADDSiL™ 8323 & ME	THYL 2-PHENYLPROPYL D	ODECYLMETHYL SILOXANE COPOLYMER		
For siloxanes:				
Effects which based on	the reviewed literature do no	ot seem to be problematic are acute toxicity, irritant		
effects, sensitization ar	nd genotoxicity.			
Some studies indicate	that some of the siloxanes main	ay have endocrine disrupting properties, and		
reproductive effects ha	ve caused concern about the	possible effects of the siloxanes on humans and the		
environment.				
Only few siloxanes are	described in the literature with	th regard to health effects, and it is therefore not		
possible to make broad	conclusions and comparisor	ns of the toxicity related to short-chained linear and		
cyclic siloxanes based	on the present evaluation. Da	ata are primarily found on the cyclic siloxanes D4		
(octamethylcyclotetrasi	loxane) and D5 (decamethyle	cyclopentasiloxane) and the short-linear HMDS		
(hexamethyldisiloxane)	These three siloxanes have	a relatively low order of acute toxicity by oral, dermal		
and inhalatory routes a	nd do not require classification	on for this effect.		
They are not found to b	e irritating to skin or eyes an	d are also not found sensitizing by skin contact. Data		
on respiratory sensitiza	tion have not been identified	Also lives is the secie tennet energy for D4 which also		
Subacute and subchroi	Subacute and subchronic toxicity studies show that the liver is the main target organ for D4 which also			
tionuces liver cell enzyn	orgon for	ontributes to the elimination of the substance from the		
D5 oxposuro by inhalat	ion is the lung. D5 has an on	zuma induction profile similar to that of D4. Subscuta		
and subchronic inhalati	on of HMDS affect in particul	ar the lungs and kidneys in rats		
None of the investigate	d siloxanes show any signs (of genotoxic effects in vitro or in vivo. Preliminary		
results indicate that D5	has a potential carcinogenic	effect.		
D4 is considered to imp	pair fertility in rats by inhalatic	on and is classified as a substance toxic to		
reproduction in categor	v 3 with the risk phrase R62	('Possible risk of impaired fertility').		
The results of a study t	o screen for oestrogen activit	y indicate that D4 has very weak oestrogenic and		
antioestrogenic activity	and is a partial agonist (enha	ances the effect of the estrogen). It is not uncommon		
for compounds that are	weakly oestrogenic to also h	nave antioestrogenic properties. Comparison of the		
oestrogenic potency of	D4 relative to ethinyloestradi	ol (steroid hormone) indicates that D4 is 585,000		
times less potent than e	ethinyloestradiol in the rat sta	in Sprague- Dawley and 3.7 million times less potent		
than ethinyloestradiol ir	n the Fisher-344 rat strain. Be	ecause of the lack of effects on other endpoints		
SiSiB SILICONFS - A nart o	of SINOPCC group.			
		西斯博有机硅		

SAFETY DATA SHEET

ADDSiL[™] 8323

version 6. i J Page 14 / 18 Revision Date 16.01.2021
--

designated to assess oestrogenicity, the oestrogenicity as mode of action for the D4 reproductive effects has been questioned. An indirect mode of action causing a delay of the LH (luteinising hormone) surge necessary for optimal timing of ovulation has been suggested as the mechanism.

Based on the reviewed information, the critical effects of the siloxanes are impaired fertility (D4) and potential carcinogenic effects (uterine tumours in females). Furthermore there seem to be some effects on various organs following repeated exposures, the liver (D4), kidney (HMDS) and lung (D5 and HMDS) being the target organs.

A possible oestrogenic effect contributing to the reproductive toxicity of D4 is debated. There seems however to be some indication that this toxicity may be caused by another mechanism than oestrogen activity.

Studies are available for linear siloxanes from an analogue group comprising di- to hexa- siloxanes, as well as key physicochemical properties, The results of the acute toxicity studies for this analogue group are in agreement: there is no evidence from any of the available studies that the substances in this group have any potential for acute toxicity (in terms of either lethality or adverse clinical effects) by any route up to and exceeding the maximum dose levels tested according to current OECD guidelines. It is therefore valid to read-across the lack of acute toxicity between the members of the group where there are data gaps.

The metabolism of silanes and siloxanes is influenced by the chemistry of silicon, and it is fundamentally different from that of carbon compounds. These differences are due to the fact that silicon is more electropositive than carbon; Si-Si bonds are less stable than C-C bonds and Si-O bonds form very readily, the latter due to their high bond energy.

Functional groups such as -OH, -CO2H, and -CH2OH are commonly seen in organic drug metabolites. If such functionalities are formed from siloxane metabolism, they will undergo rearrangement with migration of the Si atom from carbon to oxygen. Consequently, alpha hydroxysilanes may isomerise to silanols and this provides a mechanism by which very polar metabolites may be formed from highly hydrophobic alkylsiloxanes in relatively few metabolic steps.

Acute Toxicity \times Skin Irritation/Corrosion \checkmark Serious Eye Damage/Irritation \checkmark Respiratory or Skin sensitization \times Mutagenicity \times Carcinogenicity \times Reproductivity \times STOT - Single Exposure \times STOT – Repeated Exposure \times Aspiration Hazard \times

 \times – Data either not available or does not fill the criteria for classification

 \checkmark – Data available to make classification

SECTION 12: Ecological Effects

ToxicityADDSiL™ 8323ENDPOINTTEST DURATION (HR)SPECIESVALUESOURCENot AvailableNot AvailableNot AvailableNot AvailableNot Availablemethyl 2-phenylpropyl dodecylmethyl siloxane copolymer

SiSiB SILICONES - A part of SINOPCC group.



SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 15 / 18		Revision Date 16.	01.2021	
	ΤΕST DURATION (HR)	SPECIES		SOURCE	

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available

Legend: Extracted from

1. IUCLID Toxicity Data

2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity

3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated)

4. US EPA, Ecotox database - Aquatic Toxicity Data

5. ECETOC Aquatic Hazard Assessment Data

6. NITE (Japan) - Bioconcentration Data

7. METI (Japan) - Bioconcentration Data

8. Vendor Data

For siloxanes:

Environmental fate:

It is well accepted that polydimethylsiloxane fluids become permanent residents of sediment but should not exert adverse environmental effects.

Silicone fluids are very surface active because the flexible siloxane linkages permit alignment of the hydrophobic methyl substituents towards the non-polar phase, and of the polysiloxane backbone towards the polar phase. The polar medium is generally water, and a polar media to which polydimethylsiloxanes become attached may be textiles, sewage sludge, hair, algae, sediment etc. In aqueous environments, polydimethylsiloxanes are adsorbed onto sedimenting particles. Also, in the presence of nitrate ions, which exist at various concentrations in the environment, short chain siloxanes are photodegraded to the level of silicate within days.

The stability of the siloxanes, desirable from a technical point of view, makes the siloxanes very persistent, and once released to the environment the siloxanes remain for many years.

The main source of releases of siloxanes to the air is volatile siloxanes used in cosmetics, wax, polishes, and to a minor extent in several other applications. the volatile siloxanes may account for a significant part of the siloxanes used for cosmetics.

Non-volatile silicone fluids used in cosmetics, wax, polishes, cleaning products and for textile applications (softeners) will to a large extent end up in wastewater and be directed to wastewater treatment plants. The cyclic siloxanes and small-chain linear siloxanes are bioconcentrated (bioconcentration factors for long-chained siloxanes have not been assessed).

The estimated bioconcentration factors (BCF) of the small siloxanes range from 340 for HMDS to 40,000 for a phenylated trisiloxane (phenyltrimethicone). The small phenylated siloxanes seem to have very high BCF, and model estimates indicate that these substances are the most toxic for aquatic organisms. PBT profiler screening

In order to make a first comparison between the substances as to persistence, bioaccumulation and toxicity, the substances were screened using the PBT profiler developed by U.S. EPA (U.S. EPA 2003). The profiler uses a procedure to predict persistence, bioaccumulation, and toxicity of organic chemicals on the basis of the chemical structure and physical parameters of the substances combined with experimental parameters for substance with a similar structure, using a QSAR approach.



SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J	Page 16 / 18	Revision Date 16.01.2021
--------------	--------------	--------------------------

The results for six members of the siloxane family predict the highest bioconcentration factors for the two phenyl siloxanes, one order of magnitudes higher than the values for the cyclic siloxanes and two orders of magnitudes higher than the values for the small linear methyl siloxanes. The predicted toxicity is as well significantly higher (lowest ChV values) for the phenyl siloxanes. The predicted half-life is nearly the same for all substances.

Using U.S. EPA's criteria, the screening indicates that all substances are of high concern as to environmental toxicity, and that the phenyl siloxanes are considered very bioaccumulative. Ecotoxicity:

The environmental fate and effects of volatile methylsiloxanes (mainly cyclosiloxanes) and polydimethylsiloxane (PDMS) have been reported:

For octamethylcyclosiloxane:

Fish acute LC50 (14 day): rainbow trout 10 ug/l; sheepshead minnow >6.3 ug/l

Daphnia magna acute EC50 (48 h): >15 ug/l; NOEC 15 ug/l

Mysid shrimp acute LC50 (96 h): >9.1 ug/l; NOEC 9.1 ug/l

For PDMS

Daphnia magna NOEC 572 mg/kg

Physical effects such as surface entrapment have been observed when testing aquatic invertebrates in clean laboratory water, but similar effects are not expected in natural environments where a large variety of other surfaces provide opportunities for deposition.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
Bioaccumulative potential		
Ingredient	Bioaccumulation	
	No Data available for all ingredients	
Mobility in soil		
Ingredient	Mobility	
	No Data available for all ingredients	
Other adverse effects		
No data available		

SECTION 13:Disposal considerations

Waste treatment methods

Waste chemicals:

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse

Recycling



SAFETY DATA SHEET

ADDSiL™ 8323

Version 6.1JPage 17 / 18Revision Date 16.01.2021
--

Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

Where in doubt contact the responsible authority.

Recycle wherever possible or consult manufacturer for recycling options.

Consult State Land Waste Authority for disposal.

Bury or incinerate residue at an approved site.

Recycle containers if possible, or dispose of in an authorised landfill.

Contaminated packing materials:

Refer to section above

Precautions for Transport:

Refer to section above

SECTION 14:Transport Information

Labels Required

Marine Pollutant: NO

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Precautions for Transport

Suitable Containers

See section 7

SECTION 15:Regulatory Information

Safety, health and environmental regulations / legislation specific for the substance or mixture METHYL 2-PHENYLPROPYL DODECYLMETHYL SILOXANE COPOLYMER(68037-76-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS China Inventory of Existing Chemical Substances





SAFETY DATA SHEET

ADDSiL[™] 8323

Version 6.1J

Page 18 / 18

Revision Date 16.01.2021

SECTION 16:Other Information

Further information

It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

