# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C Page 1 / 10 Revision Date 06.06.2018

# SECTION 1: Identification of the substance/mixture and of the company

**Product Identifier** 

Product Name: SiSiB® MF2010-1000
Chemical Name: Polydimethylsiloxane

CAS-No.: 9006-65-9 / 9016-00-6 / 63148-62-9 EC-No.: 618-433-4 / 618-493-1 / 613-156-5

Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For Industrial Use

Details of the supplier of the safety data sheet

**Company** Nanjing SiSiB Silicones Co., Ltd.

Guanghua Sci & Tech Industrial Zone,

No. 104, Guanghua Road, Nanjing 210007, P.R.China

Email: SDS@SiSiB.com

Emergency Telephone Number: +86-25-8468-0091

#### **SECTION 2: Hazardous identification**

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Not a hazardous substance or mixture.

Label elements

Labeling according to Regulation (EC) No. 1272/2008:

No labeling according to GHS required.

Other hazards

No data available

# SECTION 3: Composition/information on ingredients

Substances

Chemical characteristics Polydimethylsiloxane

Hazardous ingredients

This material does not contain any ingredients above the permitted limit(s).

**Mixtures** 

Not applicable

# **SECTION 4: First aid measures**

### General advice



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C	Page 2 / 10	Revision Date 06.06.2018
--------------	-------------	--------------------------

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

#### After inhalation

Material cannot be inhaled under normal conditions. Get medical attention if symptoms occur.

#### After contact with the skin

After skin contact wipes off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

#### After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

#### After swallowing

No special measures are required after swallowing.

#### Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

#### Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

# **SECTION 5: Firefighting measures**

#### **Extinguishing media**

## Suitable extinguishing media:

Water mist, extinguishing powder, alcohol-resistant foam, carbon dioxide, sand.

#### Extinguishing media which must not be used for safety reasons:

Water jet.

#### Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: carbon oxides, silicon oxides, incompletely burnt hydrocarbons, toxic and very toxic fumes.

### Advice for firefighters

#### Special protective equipment for firefighting:

Use respiratory protection independent of recirculate air.

Keep unprotected persons away.

#### SECTION 6: Accidental release measures

#### Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C	.2018
--------------	-------

#### **Containment:**

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

#### Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

#### Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

# **SECTION 7: Handling and storage**

### General information:

No special protective measures required.

#### Precautions for safe handling

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

#### Precautions against fire and explosion:

Observe the general rules for fire prevention.

### Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

#### Advice for storage of incompatible materials:

Observe local/state/federal regulations.

#### Further information for storage:

Store in a dry and cool place

#### Specific end use(s)

No data available.

# **SECTION 8: Exposure Controls/Personal Protection**

#### **Control parameters**



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C Page 4 / 10 Revision Date 06.06.2018

#### Maximum airborne concentrations at the workplace

Not applicable

#### **Exposure controls**

### Exposure in the work place limited and controlled

## General protection and hygiene measures

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.

#### Personal protection equipment

#### Respiratory protection

No personal respiratory protective equipment normally required.

In case of mist, spray or aerosol exposure wears suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Filtering half-face mask, according to acknowledged standards such as EN 149.

Recommended Filter type: FFP1 or equivalent filter, according to acknowledged standards such as EN 149.

Observe the equipment manufacturer's information and wear time limits for respirators.

#### Eye protection

Recommendation: protective goggles.

#### Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of nitrile rubber

Thickness of the material: > 0, 1 mm

Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

Thickness of the material: > 0, 3 mm

Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

#### Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

# Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

# **SECTION 9: Physical and Chemical Properties**

Information on basic physical and chemical properties Appearance



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C Page 5 / 10 Revision Date 06.06.2018

Physical state / form liquid

Color colorless, clear

Odor

Odor odorless

**Odor limit** 

Odor limit no data available

**PH-Value** 

PH-Value approx.7

Melting point/freezing point

Melting point / melting range -50 °C

Initial boiling point and boiling range

Boiling point / boiling range not determinable

Flash point

Flash point > 300 °C

**Evaporation rate** 

Evaporation rate no data available

Upper/lower flammability or explosive limits

Lower explosion limit (LEL) not applicable
Upper explosion limit (UEL) not applicable

Vapor pressure

Vapor pressure not applicable

Solubility(ies)

Water solubility / miscibility virtually insoluble at 20 °C

Vapor density

Relative gas/vapor density no data known

**Relative Density** 

Density approx. 0, 97 g/cm³ (25 °C)

Partition coefficient: n-octane/water

Partition coefficient: n-octane/water No data known.

**Auto-ignition temperature** 

Ignition temperature 410 °C

**Decomposition temperature** 

Thermal decomposition Decomposition begins at > 250 °C

Viscosity

Viscosity (dynamic) 1000 mPa.s at 25 °C

Viscosity (kinematic) approx. 100 mm<sup>2</sup>/s at 25 °C

Molecular mass

Molecular mass no data available

Other information

No data available.



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C	Page 6 / 10	Revision Date 06.06.2018
--------------	-------------	--------------------------

# **SECTION 10: Stability And Reactivity**

#### **General information:**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Relevant information can possibly be found in other parts of this section.

#### Conditions to avoid

None known

#### Materials to avoid

None known

#### **Hazardous decomposition products**

If stored and handled properly: none known. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

# **SECTION 11:Toxicological Information**

#### Information on toxicological effects

#### **Acute toxicity**

#### Product details:

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD <sub>50</sub> : > 5000 mg/kg Neither mortality nor clinical signs of toxicity were observed with the given dose.	rat	literature (Polydimethylsiloxane)
dermal	LD <sub>50</sub> : > 2008 mg/kg Neither mortality nor clinical signs of toxicity were observed with the given dose.	rat	literature (Polydimethylsiloxane)

#### Skin corrosion/irritation

#### **Product details:**

Result/Effect	Species/Test system	Source
not irritating	rabbit	literature (Polydimethylsiloxane)

### Serious eye damage/eye irritation

#### Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	literature
		(Polydimethylsiloxane)

#### Respiratory or skin sensitization

# Product details:

Route of exposure Result/Effect	Species/Test system	Source
---------------------------------	---------------------	--------



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C	Page 7 / 10	Revision Date 06.06.2018
--------------	-------------	--------------------------

dermal	not sensitizing	guinea-pig;	literature
		Magnusson-Kligman	(Polydimethylsiloxane) OECD 406

# Germ cell mutagenicity

#### **Assessment:**

Based on known data a significant mutagenic potential may be excluded.

#### Product details:

Result/Effect	Species/Test system	Source
negative	mutation assay (in vitro)	literature
	bacterial cells	(Polydimethylsiloxane)
		OECD 471

# Carcinogenicity

#### **Assessment:**

Animal tests have not revealed any carcinogenic effects.

#### **Product details:**

Result/Effect	Species/Test system	Source
NOAEL: >= 1000 mg/kg	carcinogenicity study	literature
NOAEL= NOAEL (carcinogenic effects)	rat (F344)	(Polydimethylsiloxane)
	oral(feed)	
	2 a	

# Reproductive toxicity

#### **Assessment:**

Animal tests have shown no indications of possibility of damage to embryo and impairment of fertility.

#### Product details:

Result/Effect (Examinations of developmental toxicity and teratogenicity)	Species/Test system	Source
NOAEL (developmental): >= 1000 mg/kg NOAEL (maternal): >= 1000 mg/kg Symptoms/Effect: Nothing abnormal detected.	Developmental Toxicity Study rabbit oral (gavage); day 6 - 19 of gestation	literature (Polydimethylsiloxane)

# Specific target organ toxicity - single exposure

#### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

# Specific target organ toxicity - repeated exposure

#### Assessment:

For this endpoint no toxicological test data is available for the whole product.

### **Product details:**

Result/Effect	Species/Test system	Source
NOAEL: >= 1000 mg/kg	chronic study	literature
NOAEL = NOAEL (systemic effects)	rat	(Polydimethylsiloxane)
	oral (feed)	
	1 a ` ´	
	Follow-up observation	
	period: 1 a	

# **Aspiration hazard**



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C Page 8 / 10 Revision Date 06.06.	5.2018
---	--------

#### **Assessment:**

For this endpoint no toxicological test data is available for the whole product.

# Further toxicological information

Human patch test: Product displays good compatibility with the skin.

# **SECTION 12: Ecological Effects**

#### **Toxicity**

#### **Assessment:**

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

#### **Product details:**

Result/Effect	Species/Test system	Source
> 1000 mg/l (nominal) effect level > maximum achievable concentration	static (water-accommodated fraction) Fish (96 h)	literature
EC <sub>50</sub> : > 0.0001 mg/l (measured) effect level > maximum achievable concentration	static (water-accommodated fraction) Daphnia magna (48 h)	literature
IC <sub>50</sub> (growth rate): > 100000 mg/l (nominal)	static (water-accommodated fraction) Marine alga (skeleonema costatum) (72 h)	literature
NOEC: > 10000 mg/kg	feeding study rainbow trout (Oncorhynchus mykiss) (28 d)	literature
NOEC (mortality, growth, reproduction): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (21 d)	literature

# Persistence and degradability

#### **Assessment:**

Silicone content: biologically not degradable. Elimination by adsorption to activated sludge.

Polydimethylsiloxanes are degradable to a certain extent in abiotic processes.

# Bio accumulative potential

#### **Assessment:**

Polymer component: Bioaccumulation is not expected to occur.

#### Mobility in soil

### Assessment:

Polymer component: insoluble in water; adsorbs on soil.

# Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bio accumulative and toxic (PBT), or very persistent and very bio accumulative (vPvB) at levels of 0.1% or higher.

#### Other adverse effects

None known



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

	Version 5.1C	Page 9 / 10	Revision Date 06.06.2018
- 1			

# **SECTION 13:Disposal considerations**

#### Waste treatment methods

#### Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

#### Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully).

Containers may be recycled or re-used. Observe local/state/federal regulations.

Uncleaned packaging should be treated with the same precautions as the material.

#### Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the

European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

# **SECTION 14:Transport Information**

UN number; UN proper shipping name; Transport hazard class (es); Packing group

#### **Road ADR**

Not regulated for transport

#### Railway RID

Not regulated for transport

# Transport by sea IMDG-Code

Not regulated for transport

# Air transport ICAO-TI/IATA-DGR:

Not regulated for transport

#### **Environmental hazards**

Hazardous to the environment: no.

#### Special precautions for user

Relevant information in other sections has to be considered.

# Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

# **SECTION 15:Regulatory Information**



# SAFETY DATA SHEET

(EC 1907/2006) SiSiB® MF2010-1000 SILICONE FLUID

Version 5.1C	Page 10 / 10	Revision Date 06.06.2018
I VELSION 3. IC	I Paule 10 / 10	I REVISION Date 00.00.2010

#### **European Economic Area (EEA):**

**REACH** (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

## **SECTION 16:Other Information**

#### **Further information**

It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

