SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C

Page 1 / 10

Revision Date 31.05.2018

SECTION 1: Identification of the substance/mixture and of the company

Product Identifier	
Product Name:	SiSiB® MF2010-50
Chemical Name:	Polydimethylsiloxane
CAS-No.:	9006-65-9 / 9016-00-6 / 63148-62-9
EC-No.:	618-433-4 / 618-493-1 / 613-156-5
Relevant identified uses of the sub	ostance or mixture and uses advised against
Relevant applications identified	For Industrial Use
Details of the supplier of the safety	y data sheet
Company	Nanjing SiSiB Silicones Co., Ltd.
	Guanghua Sci & Tech Industrial Zone,
	No. 104, Guanghua Road, Nanjing 210007, P.R.China
	Email: SDS@SiSiB.com
Emergency Telephone Number:	+86-25-8468-0091

SECTION 2: Hazardous identification

Classification of the substance or mixture Classification (GHS): Not a hazardous substance or mixture. Label elements Labelling (GHS): No labeling according to GHS required. Other hazards No data available

SECTION 3: Composition/information on ingredients

Substances

Chemical characteristics Polydimethylsiloxane

Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

SECTION 4: First aid measures



SiSiB SILICONES - A part of SINOPCC group.



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 2 / 10	Revision Date 31.05.2018
--------------	-------------	--------------------------

General advice

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

After inhalation

Material cannot be inhaled under normal conditions. No special treatment required.

After contact with the skin

After skin contact wipes off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

After swallowing

No special measures are required after swallowing.

SECTION 5: Firefighting measures

Flammable properties:

Property:	Value:	Method:
Flash point	> 250 °C (> 482 °F)	(ISO 2592)
Flash point	> 150 °C (> 302 °F)	(EN 22719)
Boiling point / boiling range	not determinable	(EU-GL.A.2)
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Ignition temperature	395 °C (743 °F)	(EN 14522)
NFPA Hazard Class (comb. /flam. Liquid)	IIIB	

Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

Recommended extinguishing media:

Water-mist, carbon dioxide, sand, dry chemical or alcohol-resistant foam.

Unsuitable extinguishing media:

Water-spray, sharp water jet.

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide, carbon monoxide, formaldehyde, silicon dioxide and incompletely burnt hydrocarbons.

Firefighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C

Page 3 / 10

Revision Date 31.05.2018

SECTION 6: Accidental release measures

Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material. HAZWOPER PPE Level: D

Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

Maximum temperature allowed during storage and transportation: 50 °C (122 °F)

SECTION 8: Exposure Controls/Personal Protection



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 4 / 10	Revision Date 31.05.2018
Engineering controls		
Ventilation:		
Use with adequate ventila	tion.	
Local exhaust:		
Not necessary		
Personal protection equi	pment (PPE)	
Respiratory protection:		
Respiratory protection is n	ot normally required.	
Hand protection:		
Recommendation: Any lique	uid-tight rubber or vinyl g	loves.
Eye protection:		
Recommendation: Safety	glasses with side shields	
Other protective clothing	g or equipment:	
Additional protective clothi	ng or equipment is not ne	ormally required. Provide eye bath and safety shower.
General hygiene and pro	tection measures:	
When handling does not e	at, drink, smoke or apply	cosmetics. Wash thoroughly after handling.

SECTION 9: Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance		
Physical state / form:	liquid	
Color:	colorless, clear	
Odor:	odorless	
Safety parameters		
Property:	Value:	Method:
Melting point / melting range:	-55 °C (-67 °F)	
Boiling point / boiling range:	not determinable	(EU-GL.A.2)
Flash point	> 250 °C (> 482 °F)	(ISO 2592)
Flash point	> 150 °C (> 302 °F)	(EN 22719)
Ignition temperature	395 °C (743 °F)	(EN 14522)
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapor pressure:	not determined	
Density:	0.96 g/cm³ at 25 °C (77 °F)	
Water solubility / miscibility:	virtually insoluble	
PH-Value:	approx. 7	
Viscosity (dynamic):	50 mPa.s at 25 °C (77 °F)	(DIN 53019)
Viscosity (kinematic):	approx. 50 mm²/s at 25 °C (77 °F)	(DIN 53019)
Further information		
Odor limit:	no data available	

SISIE SILICONES 西斯博有机硅

SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 5 / 10	Revision Date 31.05.2018
Corrosive to Steel or Alumi	num: N	t corrosive to steel or aluminum.

Thermal decomposition:

Not corrosive to steel or aluminum. Decomposition begins at > 250 °C (> 482 °F)

SECTION 10: Stability And Reactivity

General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Conditions to avoid

None known

Materials to avoid

None known

Hazardous decomposition products

If stored and handled properly: none known. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

Further information:

Hazardous polymerization cannot occur.

SECTION 11: Toxicological Information

Information on toxicological effects

Acute toxicity

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD_{50} : > 5000 mg/kg Neither mortality nor clinical signs of toxicity were observed with the given dose.	rat	literature (Polydimethylsiloxane)
dermal	LD ₅₀ : > 2008 mg/kg Neither mortality nor clinical signs of toxicity were observed with the given dose.	rat	literature (Polydimethylsiloxane)

Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	literature
		(Polydimethylsiloxane)

Serious eye damage/eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	literature
		(Polydimethylsiloxane)

Respiratory or skin sensitization

Product details:



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Ver	sion 5.2C	Page 6 / 10	Revision Date	31.05.2018	
	Route of exposure	Result/Effect	Species/Test system	Source	

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig;	literature
		Magnusson-Kligman	(Polydimethylsiloxane) OECD 406

Germ cell mutagenicity

Assessment:

Based on known data a significant mutagenic potential may be excluded.

Product details:

Result/Effect	Species/Test system	Source
negative	mutation assay (in vitro) bacterial cells	literature (Polydimethylsiloxane) OECD 471

Carcinogenicity

Assessment:

Animal tests have not revealed any carcinogenic effects.

Product details:

Result/Effect	Species/Test system	Source
NOAEL: >= 1000 mg/kg	carcinogenicity study	literature
NOAEL= NOAEL (carcinogenic effects)	rat (F344)	(Polydimethylsiloxane)
	oral(feed)	
	2 a	

Reproductive toxicity

Assessment:

Animal tests have shown no indications of possibility of damage to embryo and impairment of fertility.

Product details:

Result/Effect (Examinations of developmental toxicity and teratogenicity)	Species/Test system	Source
NOAEL (developmental): >= 1000 mg/kg NOAEL (maternal): >= 1000 mg/kg Symptoms/Effect: Nothing abnormal detected.	Developmental Toxicity Study rabbit oral (gavage); day 6 - 19 of gestation	literature (Polydimethylsiloxane)

Specific target organ toxicity - single exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Specific target organ toxicity - repeated exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Product details:

Result/Effect	Species/Test system	Source
NOAEL: >= 1000 mg/kg	chronic study	literature
NOAEL = NOAEL (systemic effects)	rat	(Polydimethylsiloxane)
	oral (feed)	
	1 a	
	Follow-up observation	
	period: 1 a	

Aspiration hazard



SAFETY DATA SHEET SISIB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 7 / 10	Revision Date 31.05.2018
--------------	-------------	--------------------------

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Further toxicological information

No component of this product presents at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product presents at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: Human patch test: Product displays good compatibility with the skin.

SECTION 12: Ecological Effects

Toxicity

Assessment:

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

Result/Effect	Species/Test system	Source
> 1000 mg/l (nominal) effect level > maximum achievable concentration	static (water-accommodated fraction) Fish (96 h)	literature
EC ₅₀ : > 0.0001 mg/l (measured) effect level > maximum achievable concentration	static (water-accommodated fraction) Daphnia magna (48 h)	literature
IC_{50} (growth rate): > 100000 mg/l (nominal)	static (water-accommodated fraction) Marine alga (skeleonema costatum) (72 h)	literature
NOEC: > 10000 mg/kg	feeding study rainbow trout (Oncorhynchus mykiss) (28 d)	literature
NOEC (mortality, growth, reproduction): > 500 mg/kg The exposure to treated sediment did not result in effects.	exposure via sediment Daphnia magna (21 d)	literature

Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Elimination by adsorption to activated sludge.

Polydimethylsiloxanes are degradable to a certain extent in abiotic processes.

Bio accumulative potential

Assessment:

Polymer component: Bioaccumulation is not expected to occur.

Mobility in soil

Assessment:

Polymer component: insoluble in water; adsorbs on soil.

Other adverse effects



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C

Page 8 / 10

Revision Date 31.05.2018

None known

SECTION 13:Disposal considerations

Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include e.g., landfill or incineration.

Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14:Transport Information

US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport.

Transport by sea IMDG-Code

Valuation: Not regulated for transport.

Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport.

SECTION 15:Regulatory Information

U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 Components

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazards

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimums levels.



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 9 / 10	Revision Date 31.05.2018

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

U.S. State regulations

California Proposition 65 Carcinogens:

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

This material does not contain any chemicals known to the State of California to cause reproductive effects.

Massachusetts Substance List:

This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea):

ECL (Existing Chemicals List): This product is listed in, or complies with, the substance inventory. **Japan:**

ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.

Australia:

AICS (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.

People's Republic of China:

IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.

Canada:

DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory. **Philippines:**

PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.

United States of America (USA):

TSCA (Toxic Substance Control Act Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory.

Taiwan (Republic of China):

TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: Taiwan REACH requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.



SAFETY DATA SHEET

SiSiB® MF2010-50 SILICONE FLUID

Version 5.2C	Page 10 / 10	Revision Date 31.05.2018
--------------	--------------	--------------------------

European Economic Area (EEA):

REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

SECTION 16:Other Information

Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

