

SiSiB® PC16467

Silicone Elastomer Blend

*INCI: Cyclopentasiloxane (and)
Vinyl dimethicone/Dimethicone Ethoxy Glucoside Crosspolymer*

INTRODUCTION

SiSiB® PC16467 is a mixture of high molecular weight Vinyl dimethicone/ Dimethicone Ethoxy Glucoside Crosspolymer in Cyclopentasiloxane which is a transparent gel having self-emulsifying effect due to Glucose, which allow it to be formulated into W/O emulsions, W/Si emulsions, O/W emulsions to provide dry smoothness and a light silky skin, non-greasy feel.

ADVANTAGES

- ☐ Wide and natural source of raw materials
- ☐ Self-emulsifying effect ,low-temperature processing
- ☐ Acts as a thickening agent for W/O and W/Si formulations
- ☐ Provides dry smoothness and a light silky skin feel

TYPICAL PHYSICAL PROPERTIES

Appearance	Colorless and transparent gel
Non-volatile content	15~20 (% , w/w)
Viscosity(S94, 2.5RPM, 25°C)	30,000~100,000cSt

APPLICATIONS

SiSiB® PC16467 can be used in various kinds of personal care products such as facial mask, water cream and essence.

- ☐ How to use:

This product could be dispersed into the oil-phase using simple mixing.

SiSiB® PC16467 can be added to the oil phase or silicone phase in an emulsion formulation.

SiSiB® PC16467 can be post-added to emulsions provided the emulsion is viscous enough for the products to be dispersed.

SiSiB® PC16467

Silicone Elastomer Blend

*INCI: Cyclopentasiloxane (and)
Vinyl dimethicone/Dimethicone Ethoxy Glucoside Crosspolymer*

For ease of use, blending with dimethicone or cyclomethicone may reduce this product's viscosity.

The material of SiSiB® PC16467 should be processed in an enclosed vessel to prevent the cyclopentasiloxane from volatilizing when heat is used.

The recommended processing temperature is not over 60°C.

SiSiB® PC16467 would become very thick or even lumpy after a period of time. This is normal and it will recovery to original state after slightly agitate.

□ Recommend Dosage:

The recommended usage level is 1-20%.

PACKING AND STORAGE

SiSiB® PC16467 is supplied in 20Kg plastic drum or 200Kg steel drum.

In the original unopened packaging, SiSiB® PC16467 has a shelf life of two years in a dry and cool place. The storage temperature could not be over 60°C.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.