

Version 5.1R	Page 1 / 11	Revision Date 23.07.2018
--------------	-------------	--------------------------

SECTION 1: Identification of the substance/mixture and of the company

Product Identifier

Product Name: SiSiB® PC2521
 Chemical Name: 3-Ureidopropyltriethoxysilane (50% Methanol)
 CAS No.: 23779-32-0

Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For industrial use
 Coupling agent
 Crosslinking agents
 Surface modifier

Details of the supplier of the safety data sheet

Company Nanjing SiSiB Silicones Co., Ltd.
 Guanghua Sci & Tech Industrial Zone,
 No. 104, Guanghua Road, Nanjing 210007, P.R.China
 Email: SDS@SiSiB.com

Emergency Telephone Number: +86-25-8468-0091

SECTION 2: Hazardous identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Category 2	H225
Acute toxicity, Oral	Category 3	H301
Acute toxicity, Inhalation	Category 3	H331
Acute toxicity, Dermal	Category 3	H311
Specific target organ toxicity - single exposure	Category 1	H370

Label elements

Labelling according Regulation (EC) No 1272/2008

Statutory basis EU-CLP as per Regulation (EU) No. 1272/2008

Pictogram



Signal word Danger

Hazard statement(s)

Version 5.1R	Page 2 / 11	Revision Date 23.07.2018
--------------	-------------	--------------------------

H225	Highly flammable liquid and vapor.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled
H370	Causes damage to organs.
Precautionary statement Prevention	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P280	Wear protective gloves/ protective clothing.
Precautionary statement Reaction	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P302 + P352	IF ON SKIN: Wash with plenty of water/ soap.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P307 + P311	IF exposed or concerned: Call a POISON CENTER/doctor.
Precautionary statement Storage	
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Chemical nature

Silane preparation

Substances

-

Mixtures

Information on ingredients / Hazardous components as per EU-CLP Regulation (EC) No. 1272/2008

Methanol > 20%		
CAS-No. 67-56-1 EC-No. 200-659-6		
Flammable liquids	Category 2	H225
Acute toxicity (Oral)	Category 3	H301
Acute toxicity (Dermal)	Category 3	H311
Acute toxicity (Inhalation)	Category 3	H331
Specific target organ toxicity - single exposure	Category 1	H370

Texts of H phrases, see in Chapter 16

SECTION 4: First aid measures

Description of first aid measures

Take off all contaminated clothing immediately.

If inhaled

If aerosol or mists are formed:

Move victims into fresh air.

In case of persistent discomfort: Consult doctor immediately.

In case of skin contact

Wash off immediately with plenty of water.

Consult a doctor in the event of permanent skin irritation.

In case of eye contact

Keeping eyelid open, immediately rinse thoroughly for at least 5 minutes using plenty of water or, if necessary, eye rinsing solution.

Consult an ophthalmologist.

If swallowed

Have the mouth rinsed with water.

Only when patient fully conscious:

Have patient drink plenty of water in small sips.

Call a physician immediately.

Most important symptoms and effects, both acute and delayed**Symptoms**

After absorbing large amounts of substance:

Liberation of reaction products (Methanol) can lead to symptoms of poisoning.

Possible signs of poisoning:

daze, dizziness, nausea, colicky abdominal pain, respiratory disturbance.

Symptoms upon increasing intoxication: dysopia, loss of eyesight.

Indication of any immediate medical attention and special treatment needed

If required, therapy of irritative effect.

Treatment:

Early endoscopy in order to assess mucosa lesions in the oesophagus and stomach which may appear. If necessary, aspirate leftover substance.

Detection of substance (Methanol) possible in:

Blood

Antidote treatment: ethanol.

SECTION 5: Firefighting measures**Extinguishing media****Suitable extinguishing media**

water spray, foam, Carbon dioxide (CO₂), dry powder

Unsuitable extinguishing media

Version 5.1R

Page 4 / 11

Revision Date 23.07.2018

High volume water jet

Special hazards arising from the substance or mixture

In case of fire cool endangered containers with water.

Closed container may rupture if strongly heated.

Advice for firefighters

Water used to extinguish fire should not enter drainage systems, soil or stretches of water.

Ensure there are sufficient retaining facilities for water used to extinguish fire.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In case of fire: wear a self-contained respiratory apparatus

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment.

Keep away from sources of ignition - No smoking.

Ensure adequate ventilation.

Environmental precautions

Do not allow entrance in sewage water, soil stretches of water, groundwater, drainage systems.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Fill into marked, sealable containers.

To be disposed of in compliance with existing regulations.

Reference to other sections

Wear personal protective equipment; see section 8.

Disposal considerations; see section 13.

SECTION 7: Handling and storage**Precautions for safe handling**

Provide good ventilation or extraction.

Application, processing: Extraction at the emission source required.

Conditions for safe storage, including any incompatibilities**Advice on protection against fire and explosion**

Take precautionary measures against static charges; keep away from sources of ignition.

Explosion protection equipment required.

Danger of explosion from residual product fumes; therefore avoid spark production through cutting, grinding, or welding work in the area of the container.

When repairs of the production system are to be made (e.g. welding work), the section to be repaired must

Version 5.1R

Page 5 / 11

Revision Date 23.07.2018

be essentially free of product.

Storage

Keep containers tightly closed in a cool, well-ventilated place.

The formation of carbamate must be anticipated if stored above room temperature.

Protect from moisture.

Comply with storage regulations and regulations prohibiting storage of hazardous substances in non-stationary containers in the same room (TRGS 510).

Specific end use(s)

No further information available

Applications; see Section 1.

SECTION 8: Exposure Controls/Personal Protection**Control parameters****Exposure controls****Engineering measures**

Provide good ventilation or extraction.

Personal protective equipment**Respiratory protection**

In case of dusts/vapors/aerosols being formed or if the limit values like TLV are exceeded: use respiratory equipment with suitable filter (filter type A) or wear a self-contained respiratory apparatus

Use only respiratory protection equipment with CE-symbol including four digit test number.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Note time limit for wearing respiratory protective equipment.

Hand protection

Glove material for example, butyl-rubber

Material thickness 0,5 mm

Break through time \geq 480 min

Glove material for example, Fluorinated rubber (Viton)

Material thickness 0,4 mm

Break through time \geq 240 min

Selection of protective gloves to meet the requirements of specific workplaces.

Suitability for specific workplaces should be clarified with protective glove manufacturers.

The information is based on our own tests, references from the literature and information from glove manufacturers, or derived by analogy with similar materials.

Please observe that the daily duration of usage of a chemical protective glove is in practice far shorter due to the many influencing factors (e.g. temperature, mechanical strain on the glove material) than the permeation time determined acc. EN 374.

Version 5.1R	Page 6 / 11	Revision Date 23.07.2018
--------------	-------------	--------------------------

Eye protection

Safety glasses

Skin and body protection

Flame retardant antistatic protective clothing.

(Solvent-resistant)

Hygiene measures

When using, do not eat, drink or smoke. Wash face and/or hands before break and end of work.

Remove immediately all contaminated clothing.

Wash contaminated clothing before re-use.

Protective measures

Handle in accordance with good industrial hygiene and safety practice.

The personal protective equipment used must meet the requirements of directive 89/686/EEC and amendments (CE certification).

If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.

If there is the possibility of skin/eye contact, the indicated hand/eye/body protection should be used.

Do not breathe in vapors or aerosols.

Avoid contact with skin and eyes.

SECTION 9: Physical and Chemical Properties

Information on basic physical and chemical properties

Form	liquid
Color	colorless
Physical state	liquid
Odor	alcoholic
Odor Threshold	no data available
pH	no data available
Boiling point/range	73,4 °C (1013 hPa)
	Method: OECD TG 103
Flash point:	13 °C
	Method: DIN EN ISO 13736
Evaporation rate	no data available
Lower explosion limit	5,5 %(V)
	tested substance:
	methanol
Upper explosion limit	44 %(V)
	tested substance:
	methanol
Vapor pressure	ca. 120 hPa (20 °C)

Version 5.1R	Page 7 / 11	Revision Date 23.07.2018
--------------	-------------	--------------------------

Density	ca. 0,92 g/cm ³ (20 °C) Method: OECD Test Guideline 109
Water solubility	partly miscible partial decomposition by hydrolysis
Partition coefficient: n-octanol/water	not determined
Thermal decomposition	not determined
Viscosity, dynamic	not determined
Other safety information	
Ignition temperature	425 °C Method: DIN 51 794

SECTION 10: Stability And Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapors may form explosive mixture with air.

Conditions to avoid

Hydrolyses on contact with water. In the presence of oxygen and heat, the ethanol forming during the reaction may produce acetaldehyde.

Material may form acetaldehyde when heated with inorganic pigments in the presence of air.

Incompatible materials

water

Hazardous decomposition products

Methanol in case of hydrolysis.

Alcohol formed by hydrolysis lowers the flash point of the product.

SECTION 11: Toxicological Information

Information on toxicological effects

No toxicological studies are available on the mixture.

Acute oral toxicity

Acute toxicity estimate : 200 mg/kg

Method: Calculation method

Acute inhalation toxicity

Acute toxicity estimate : 6 mg/l / 4 h / vapor

Method: Calculation method

Version 5.1R

Page 8 / 11

Revision Date 23.07.2018

Acute dermal toxicity

Acute toxicity estimate : 601 mg/kg

Method: Calculation method

Assessment of STOT single exposure

Causes damage to organs.

Human experience

Liver and kidney injuries may occur.

Further information

The properties of this product which are hazardous to health have been calculated as per regulation (EC) No. 1272/2008. See section 2 "Hazards Identification".

SECTION 12: Ecological Effects**Toxicity**

No ecotoxicological studies are available on the mixture.

Persistence and degradability

Biodegradability No data available

Bioaccumulative potential

Bioaccumulation No data available

Mobility in soil

Mobility No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Further Information

An Expert Judgment stated that no classification is necessary based on present knowledge.

SECTION 13: Disposal considerations**Waste treatment methods****Product:**

With respect to local regulations, e.g. dispose of to suitable waste incineration plant.

Uncleaned packaging

Do not reuse empty containers and dispose of in accordance with the regulations issued by the appropriate local authorities.

If there is product residue in the emptied container, follow directions for handling on the container's label.

Incorrect disposal or reuse of this container is illegal and can be dangerous.

Other countries: observe the national regulations.

Version 5.1R

Page 9 / 11

Revision Date 23.07.2018

Waste Key Number

No waste key number as per the European Waste Types List can be assigned to this product, since such classification is based on the (as yet undetermined) use to which the product is put by the consumer.

The waste key number must be determined as per the European Waste Types List (decision on EU Waste Types List 2000/532/EC) in cooperation with the disposal firm / producing firm / official authority.

SECTION 14: Transport Information**Transport on land (ADR/RID/GGVSEB)**

UN number: UN 1230
 UN proper shipping name: METHANOL SOLUTION
 Transport hazard class(es): 3 (6.1)
 Packing group: II
 Environmental hazards: --
 Special precautions for user: Yes
 ADR: Tunnel Restriction Code: (D/E)
 Keep separate from foodstuffs, luxury foods, feedstuffs

Inland waterway transport (ADN/GGVSEB (Germany))

UN number: UN 1230
 UN proper shipping name: METHANOL SOLUTION
 Transport hazard class(es): 3 (6.1)
 Packing group: II
 Environmental hazards: --
 Special precautions for user: Yes
 Keep separate from foodstuffs, luxury foods, feedstuffs

Air transport ICAO-TI/IATA-DGR

UN number: UN 1230
 UN proper shipping name: Methanol Solution
 Transport hazard class(es): 3 (6.1)
 Packing group: II
 Environmental hazards: --
 Special precautions for user: Yes
 IATA-C: Subsidiary risk: 6.1 (not to label)
 FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity - Regulation!
 IATA-P: Subsidiary risk: 6.1 (not to label)
 FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity- Regulation!
 Keep separate from foodstuffs, luxury foods, feedstuffs

Sea transport IMDG-Code/GGVSee (Germany)

UN number: UN 1230
 UN proper shipping name: METHANOL SOLUTION

Version 5.1R	Page 10 / 11	Revision Date 23.07.2018
--------------	--------------	--------------------------

Transport hazard class(es): 3 (6.1)

Packing group: II

Environmental hazards: --

Special precautions for user: Yes

EmS: F-E,S-D

Clear of living quarters.

FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity -Regulation!

Keep separate from foodstuffs, luxury foods, feedstuffs

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

for transport approval see regulatory information

SECTION 15:Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National legislation

Major Accident Hazard Legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

listing: ACUTE TOXIC (H2)

quantity: 50 t 200 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

listing: FLAMMABLE LIQUIDS (P5c)

quantity: 5000 t 50000 t

ATTENTION: Classification into hazard category P5c is a minimum classification. Only the operator may estimate if the product is covered by hazard category P5a or P5c. For P5a and P5b different qualifying quantities are valid.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

listing: Methanol (22)

quantity: 500 t 5000 t

Chemical safety assessment

No chemical safety assessment is required for this product.

SECTION 16:Other Information

Relevant H phrases from chapter 3

H225

Highly flammable liquid and vapor.

H301

Toxic if swallowed.

Version 5.1R	Page 11 / 11	Revision Date 23.07.2018
--------------	--------------	--------------------------

H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Further information

It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.