SiSiB® PC4300

Gamma-Methacryloxypropyl methyldimethoxysilane

CHEMICAL STRUCTURE

$$\begin{array}{c|c} & O & CH_3 \\ H_2C & C & C & CH_2)_3 & Si & OCH_3 \\ \hline & CH_3 & OCH_3 & OCH_3 \end{array}$$

INTRODUCTION

SiSiB® PC4300 is a methacryl-functional silane; it is a clear, light and heat sensitive liquid with a faintly sweet odour.

SiSiB® PC4300 is used as adhesion promoter at organic/inorgainc interfaces, as surface modifier (e.g. imparting water repellency, organophilic surface adjustment) or as crosslinking of polymers). It is used as a coupling agent to improve the physical and electrical properties of glass-reinforced and mineral-filled thermosetting resins under exposure to heat and/or moisture. It is typically employed as a blend additive in resin systems that cure via a free radical mechanism (e.g. polyester, acrylic) and in filled or reinforced thermoplastic polymers, including polyolefins and polyurethanes. It is also used to functionalize resins via radical initiated processes - copolymerization or grafting and to modify surfaces.

TYPICAL PHYSICAL PROPERTIES

CAS No.	14513-34-9
EINECS No.	238-518-6
Formula	$C_{10}H_{20}O_4Si$
Molecular Weight	232.35
Boiling Point	83°C [3mmHg]
Flash Point	115°C
Color and Appearance	Colorless transparent liquid
Density _{25/25°C}	1.01
Refractive Index	1.433 [25°C]
Min. Purity	98.0%

SINOPCC GROUP

AddSil, CoatSil, Kolark, PowSil, SinoSil, SiSiB, WinSil: Trademark of SINOPCC Group Limited or its affiliated. © 2018 SINOPCC Group Limited. All rights reserved. For further information, please see www.SiSiB.com.

SiSiB® PC4300

Gamma-Methacryloxypropyl methyldimethoxysilane

Solubility: SiSiB® PC4300 is soluble in methanol, ethanol, isopropanol, acetone, benzene, toluene, and xylene. After hydrolysis, it is soluble in water with adequate stirring if the pH is adjusted to 4.0. Hydrolysis releases methanol.

SiSiB® PC4300 shows copolymerization or grafting reactions when catalyzed by (organic) initiator systems, e.g. peroxides or by radiation (e.g. UV).

APPLICATIONS

SiSiB® PC4300 can improve strength as glass fiber size composite in reinforced polyester composites.

SiSiB® PC4300 can enhance initial and wet strength of reinforced polyester resin composites.

SiSiB® PC4300 can enhance the wet electrical properties of many mineral-filled and reinforced composites.

SiSiB® PC4300 crosslinked acrylic type resins can improve adhesion and durability of adhesives and coatings.

PACKING AND STORAGE

SiSiB® PC4300 is supplied in 25Kg plastic drum, 200Kg steel drum or 1000Kg IBC container.

In the unopened original container SiSiB® PC4300 has a shelf life of 9 months in a dry and cool place.

Notes

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

SINOPCC GROUP

AddSil, CoatSil, Kolark, PowSil, SinoSil, SiSiB, WinSil: Trademark of SINOPCC Group Limited or its affiliated. © 2018 SINOPCC Group Limited. All rights reserved. For further information, please see www.SiSiB.com.

SiSiB® PC4300

Gamma-Methacryloxypropyl methyldimethoxysilane

Please send all technical questions concerning quality and product safety to: silanes@SiSiB.com.



AddSil, CoatSil, Kolark, PowSil, SinoSil, SiSiB, WinSil: Trademark of SINOPCC Group Limited or its affiliated. © 2018 SINOPCC Group Limited. All rights reserved. For further information, please see www.SiSiB.com.